



DM-LWET

Altezza utile mm. 450

TIPOLOGIA MATERIALE E STANDARD QUALITATIVI

- Laterizio
- Cemento
- Cemento armato

INDICAZIONI DI TAGLIO

Taglio a umido



Tabella varianti articolo

Art./Item	Ø (mm.)	Attacco	Sett. Q.tà	Dim.settore
56590	52	1 1/4	5	24x3,5x10
56591	62	1 1/4	6	24x3,5x10
56592	72	1 1/4	7	24x3,5x10
56593	82	1 1/4	8	24x3,5x10
56594	102	1 1/4	9	24x3,5x10
56595	112	1 1/4	9	24x3,5x10
56596	122	1 1/4	10	24x3,5x10
56597	127	1 1/4	10	24x3,5x10
56598	132	1 1/4	11	24x3,5x10
56599	152	1 1/4	12	24x4,0x10
56600	162	1 1/4	12	24x4,0x10
56601	202	1 1/4	15	24x4,0x10
56602	92	1 1/4	8	24x3,5x12
56603	142	1 1/4	11	24x4,0x12
56604	32	1 1/4	3	24x3,5x12
56605	42	1 1/4	4	24x3,5x12
56608	181	1 1/4	13	24x4,0x12
56609	226	1 1/4	16	24x4,0x12
56610	250	1 1/4	17	24x4,0x12
56611	275	1 1/4	19	24x4,0x12
56612	300	1 1/4	21	24x4,0x12
56612	300	1 1/4	21	24x4,0x12